SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: UZIN MK 200

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

· Product category PC1 Adhesives, sealants

· Application of the substance / the mixture 1-Component STP Parquet Adhesive

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Uzin Ltd.

Unit 2, Mitchell Court

Central Park, Rugby

Warwickshire, CV23 OUY,

Telephone +44 (0) 1788 530 080

Fax +44 (0) 1788 536508

Email info@uzin.co.uk

· Further information obtainable from:

Product safety department email: msds.info@uzin-utz.com

· 1.4 Emergency telephone number:

Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333



SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS07
- · Signal word Warning

· Hazard-determining components of labelling:

N-(*3-*(*trimethoxysilyl*)*propyl*)*ethylenediamine*

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Trade name: UZIN MK 200

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

1-Component MSP Parquet Adhesive based on modified silane prepolymers and inorganic fillers (chalk).

· Dangerous components:		
EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine ♦ Eye Dam. 1, H318; ♦ Skin Sens. 1, H317	1 - <3%
Reg.nr.: 01-2119970215-39 CAS: 2768-02-7	trimethoxyvinylsilane	1 - <3%
EINECS: 220-449-8 Reg.nr.: 01-2119513215-52	♠ Flam. Liq. 3, H226; ♠ Acute Tox. 4, H332	
CAS: 41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<0.25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Trade name: UZIN MK 200

See Section 13 for disposal information.

(Contd. of page 2)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Ensure adequate ventilation

Wash hands before breaks and at the end of work.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from humidity and water.

Once opened unfinished quantities must be stored in airtight packaging conditions.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 2768-02-7 trimethoxyvinylsilane

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

(Methanol)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Occupational exposure limits (OEL) are demonstrably maintained during application. Therefore, no respiratory protection is necessary.

· Protection of hands:



PVC or PE gloves

· Material of gloves

PVC or PE gloves

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Printing date 05.07.2017 *Version No.* 4 *Revision:* 05.07.2017

Trade name: UZIN MK 200

· Eye protection: Safety glasses

(Contd. of page 3)

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Colour:
Codour:
Codour:
Codour:
Codour:
Codour threshold:
Codour thres

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

• Flash point: $> 100 \, ^{\circ}C$

· Flammability (solid, gas): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapour pressure: Not determined.

Density at 20 °C: 1.72 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic at 20 °C: 100000 mPas (Brookfield, RV7, 20 rpm)

Kinematic: Not determined.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Product hydrolyzes to form methanol on exposure to water or humid air.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: During storage, avoid moisture contamination.

(Contd. on page 5)

Trade name: UZIN MK 200

(Contd. of page 4)

· 10.6 Hazardous decomposition products: Methanol possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$
- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water course or sewage system.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Let product residues harden in open container, then dispose of as construction waste.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, ADN, IMDG, IATA

Void

(Contd. on page 6)

Trade name: UZIN MK 200

	(Contd. of pag
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Anno Marpol and the IBC Code	e x II of Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207

E-Mail: msds.info@uzin-utz.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 7)

Page 7/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.07.2017 Version No. 4 Revision: 05.07.2017

Trade name: UZIN MK 200

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

 \cdot * Data compared to the previous version altered.

(Contd. of page 6)