

# PRODUCT DATA SHEET

FOR  
PROFESSIONAL  
USE ONLY



Premium Initial and Maintenance Cleaner

# UZIN Hardwood Care

Emulsion to improve the wear life of sealed wooden floors

## Description:

High quality, water-based emulsion for care and protection of floors. Improves the seal and appearance of the surface and extends the wear life of the flooring. Especially suitable for the initial and maintenance of all sealed wood- and cork floors.

## Suitable for:

- ▶ Sealed wood floorings
- ▶ Sealed cork floorings
- ▶ Pre-finished wood floorings
- ▶ Linoleum
- ▶ PVC



## Product benefits / properties:

- ▶ Extremely hard wearing capability
- ▶ Slip-resistant
- ▶ Abrasion-resistant, long-term protection
- ▶ Extends the wear life of the floor
- ▶ Fast drying

## Technical Data:

Packaging:	5 litre plastic canister 0.75 litre plastic bottle
Shelf life:	minimum 24 months
Colour:	transparent
Consumption:	Initial clean: approx. 7 – 10 ml/m <sup>2</sup> Maintenance: approx. 100 – 250 ml / 10 l water
Working temperature:	18 – 25 °C
Working time:	approx. 60 minutes*
Set to traffic:	after approx. 60 minutes*

\*At 21 °C and 65 % relative humidity.



UZIN | A brand of Uzin Utz Group

DE | Uzin Utz AG | Dieselstraße 3 | 89079 Ulm | Telefon +49 731 4097-0 | Telefax +49 731 4097-110 | E-Mail info@uzin.de | Internet www.uzin.com

GB | Uzin Utz UK Ltd. | Unit 2, Mitchell Court | Central Park, Rugby, CV23 0UY | Tel.: +44 1788 530 080 | Fax: +44 1788 536 508 | E-mail: uzin.uk@uzin-utz.com | Internet www.uzin.co.uk

FR | Uzin Utz France SAS | 6 avenue du Professeur André Lemierre | 75980 Paris Cedex 20 | Téléphone +33 141632720 | Téléfax +33 141632721 | E-mail uzin.fr@uzin-utz.com | Internet www.uzin.fr

## Substrate preparation:

The floor must be dry, clean and free of all contaminants such as grease, oil, paint and wax. Remove traces of dirt and dust by using a mop, broom or vacuum cleaner.

## Application:

- ▶ Lightly shake the container for a short time before use.
- ▶ Initial treatment: Apply a undiluted, thin and even coat of UZIN Hardwood Care using a sponge or mop. Apply at a rate of 10 ml per square metre. No buffing is required. After approx. 60 minutes, the surface can be used.
- ▶ Maintenance: Dilute approx. 100 – 250 ml UZIN Hardwood Care with 10 litres of water and apply thinly with a sponge, cloth or mop. After 60 minutes, the surface can be used. This maintenance should be carried out as required.
- ▶ Allow surface to dry for 60 minutes. Rinse sponge, cloth or mop with water.

## Important notes:

- ▶ Shelf life minimum 24 month in original packaging when stored in relatively cool conditions. Protect from freezing. Carefully and tightly reseal opened canisters and use the content as quickly as possible. Allow product to reach room temperature before use.
- ▶ Leave freshly sealed surfaces until fully hardened (depending on the seal system used) before treating with UZIN Hardwood Care.
- ▶ Regular maintenance with UZIN Hardwood Care improves the appearance and increases the wear life of the sealed surface.
- ▶ Leave freshly sealed surfaces at least one day before covering with carpeting or other floor coverings, or loading with heavy objects.

## Protection of the Workplace and the Environment:

Water based cleaner. Non-flammable. Use of barrier cream and ventilation of the work area are recommended. Observe safety information on product label as well as safety data sheet.

## Disposal:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, drip-free plastic containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.